



<b>THOMSON</b>  <b>DELPHION</b>		<b>RESEARCH</b> <a href="#">Get It</a>   <a href="#">Find It</a>   <a href="#">Apply It</a>   <a href="#">My Account</a>   <a href="#">Products</a>	<b>PRODUCTS</b> Search: <a href="#">Quick/Number</a> <a href="#">Boolean</a> <a href="#">Advanced</a>	<b>INSIDE DELPHION</b>
--	--	--	--	------------------------

## The Delphion Integrated View

Get Now: <input checked="" type="checkbox"/> PDF   <a href="#">More choices...</a>	Tools: Add to Work File: <a href="#">Create new Wor</a>
View: <a href="#">INPADOC</a>   Jump to: <a href="#">Top</a> 	Go to: <a href="#">Derwent...</a>  <a href="#">Ema</a>

Title: **JP4206366A2: FLAT BATTERY**

Country: **JP** Japan

Kind: **A**

Inventor: **NAKAI KENJI;  
HIGASHIMOTO KOJI;  
HIRONAKA KENSUKE;  
HAYAKAWA TAKUMI;  
KOMAKI AKIO;  
NAKANAGA TAKEFUMI;  
TANIGUCHI MASATOSHI;**

Assignee: **SHIN KOBE ELECTRIC MACH CO LTD.  
OTSUKA CHEM CO LTD.**  
[News, Profiles, Stocks and More about this company.](#)



Published / Filed: **1992-07-28 / 1990-11-30**

Application Number: **JP1990000333743**

IPC Code: **H01M 10/40; H01M 4/02;**

Priority Number: **1990-11-30 JP1990000333743**

Abstract:

... PURPOSE: To prevent the aggravation of the battery performance by laminating a flat positive electrode active material and a negative electrode active material through a solid electrolyte, covering these generating elements with a collector, divisionally forming the positive electrode active material on the collector, and sealing the peripheral part by a sealing material.

... CONSTITUTION: On a stainless foil used as both a battery sheath and a collector 1, an aqueous solution of vanadium pentoxide which is a positive electrode material 2 is finely applied by means of screen printing, dried and heated. For example, a 1,2-dimethoxyethane(DME) solution of a polyphosphadine derivative in which 1mol/l of lithium perchlorate is dissolved is applied thereon by means of screen printing, and the DME is evaporated to form a solid electrolyte 3. A metal lithium foil is stuck thereon as a negative electrode active material 4, and further covered with the stainless foil of a collector 1', and the peripheral part is thermally fused by a sealing material 5 such as a modified polyethylene resin and sealed. Thus, the aggravation of the battery performance can be prevented.

... COPYRIGHT: (C)1992,JPO&Japio.

Family: **None**

Other Abstract **None**

Info:



[Nominate](#)

[this for the Gallery...](#)

© 1997-2003 Thomson Delphion

[Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact](#)

<b>THOMSON</b>  <b>DELPHION</b>				<b>RESEARCH</b>	<b>PRODUCTS</b>	<b>INSIDE DELPHION</b>
<a href="#">Home</a>	<a href="#">About Delphion</a>	<a href="#">Help &amp; Support</a>	<a href="#">My Account</a>   <a href="#">Products</a>	Search: <a href="#">Quick/Number</a> <a href="#">Boolean</a> <a href="#">Advanced</a>		

## The Delphion Integrated View

 Get Now: ☒ PDF | [More choices...](#)

 Tools: [Add to Work File](#): [Create new Wor](#)

 View: [INPADOC](#) | Jump to: [Top](#)  Go to: [Derwent...](#)
 [Ema](#)

 Title: **JP4206366A2: FLAT BATTERY**

 Country: **JP. Japan.**

 Kind: **A.**

 Inventor: **NAKAI KENJI;  
HIGASHIMOTO KOJI;  
HIRONAKA KENSUKE;  
HAYAKAWA TAKUMI;  
KOMAKI AKIO;  
NAKANAGA TAKEFUMI;  
TANIGUCHI MASATOSHI;**

 Assignee: **SHIN KOBE ELECTRIC MACH CO LTD.  
OTSUKA CHEM CO LTD.**  
[News, Profiles, Stocks and More about this company.](#)

 Published / Filed: **1992-07-28 / 1990-11-30.**

 Application Number: **JP1990000333743**

 IPC Code: **H01M 10/40; H01M 4/02;**

 Priority Number: **1990-11-30 JP1990000333743**

Abstract:

**PURPOSE:** To prevent the aggravation of the battery performance by laminating a flat positive electrode active material and a negative electrode active material through a solid electrolyte, covering these generating elements with a collector, divisionally forming the positive electrode active material on the collector, and sealing the peripheral part by a sealing material.


**CONSTITUTION:** On a stainless foil used as both a battery sheath and a collector 1, an aqueous solution of vanadium pentoxide which is a positive electrode material 2 is finely applied by means of screen printing, dried and heated. For example, a 1,2-dimethoxyethane(DME) solution of a polyphosphadine derivative in which 1mol/l of lithium perchlorate is dissolved is applied thereon by means of screen printing, and the DME is evaporated to form a solid electrolyte 3. A metal lithium foil is stuck thereon as a negative electrode active material 4, and further covered with the stainless foil of a collector 1', and the peripheral part is thermally fused by a sealing material 5 such as a modified polyethylene resin and sealed. Thus, the aggravation of the battery performance can be prevented.

**COPYRIGHT:** (C)1992,JPO&Japio.

 Family: **None**

 Other Abstract **None**

Info:



[this for the Gallery...](#)

[Nominate](#)

© 1997-2003 Thomson Delphion ... [Research Subscriptions](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact](#)



(19)

(11) Publication number: **04**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **02333743**(51) Intl. Cl.: **H01M 10/40 H01M 4/02**(22) Application date: **30.11.90**

<p>(30) Priority:</p> <p>(43) Date of application publication: <b>28.07.92</b></p> <p>(84) Designated contracting states:</p>	<p>(71) Applicant: <b>SHIN KOBE ELECTRIC LTD.</b> <b>OTSUKA CHEM CO LT</b></p> <p>(72) Inventor: <b>NAKAI KENJI</b> <b>HIGASHIMOTO KOJI</b> <b>HIRONAKA KENSUKE</b> <b>HAYAKAWA TAKUMI</b> <b>KOMAKI AKIO</b> <b>NAKANAGA TAKEFUM</b> <b>TANIGUCHI MASATOSH</b></p> <p>(74) Representative:</p>
---	---

**(54) FLAT BATTERY**


(57) Abstract:

**PURPOSE:** To prevent the aggravation of the battery performance by laminating a flat positive electrode active material and a negative electrode active material through a solid electrolyte, covering these generating elements with a collector, divisionally forming the positive electrode active material on the collector, and sealing the peripheral part by a sealing material.

**CONSTITUTION:** On a stainless foil used as both a battery sheath and a collector 1, an aqueous solution of vanadium pentoxide which is a positive electrode material 2 is finely applied by means of screen printing, dried and heated. For example, a 1,2-dimethoxyethane(DME) solution of a

polyphosphadine derivative in which 1 mol/l of lithium perchlorate is dissolved is applied thereon by means of screen printing, and the DME is evaporated to form a solid electrolyte 3. A metal lithium foil is stuck thereon as a negative electrode active material 4, and further covered with the stainless foil of a collector 1', and the peripheral part is thermally fused by a sealing material 5 such as a modified polyethylene resin and sealed. Thus, the aggravation of the battery performance can be prevented.

COPYRIGHT: (C)1992,JPO&Japio



04206366 A



(19)

(11) Publication number:

**04**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **02333743**(51) Intl. Cl.: **H01M 10/40 H01M 4/02**(22) Application date: **30.11.90**

(30) Priority:

(43) Date of application  
publication: **28.07.92**(84) Designated contracting  
states:(71) Applicant: **SHIN KOBE ELECTRIC  
LTD  
OTSUKA CHEM CO LT**(72) Inventor: **NAKAI KENJI  
HIGASHIMOTO KOJI  
HIRONAKA KENSUKE  
HAYAKAWA TAKUMI  
KOMAKI AKIO  
NAKANAGA TAKEFUM  
TANIGUCHI MASATOSH**

(74) Representative:

**(54) FLAT BATTERY**

(57) Abstract:

**PURPOSE:** To prevent the aggravation of the battery performance by laminating a flat positive electrode active material and a negative electrode active material through a solid electrolyte, covering these generating elements with a collector, divisionally forming the positive electrode active material on the collector, and sealing the peripheral part by a sealing material.

**CONSTITUTION:** On a stainless foil used as both a battery sheath and a collector 1, an aqueous solution of vanadium pentoxide which is a positive electrode material 2 is finely applied by means of screen printing, dried and heated. For example, a 1,2-dimethoxyethane(DME) solution of a

polyphosphadine derivative in which 1mol/l of lithium perchlorate is dissolved is applied thereon by means of screen printing, and the DME is evaporated to form a solid electrolyte 3. A metal lithium foil is stuck thereon as a negative electrode active material 4, and further covered with the stainless foil of a collector 1', and the peripheral part is thermally fused by a sealing material 5 such as a modified polyethylene resin and sealed. Thus, the aggravation of the battery performance can be prevented.

COPYRIGHT: (C)1992,JPO&Japio

